



testo 190-T1, testo 190-T2, testo 190-T3,
testo 190-T4, testo 190-P1



testo 191-T1, testo 191-T2, testo 191-T3,
testo 191-T4, testo 191-P1

1



www.testo.com

2



0515 1901

3



4



5




6



 testo 190-T1, testo 191-T1	47 g	IP68	-20 ... +50 °C -4 ... +122 °F	0,1 °C 0.1 °F	-50 ... +140 °C -58 ... +284 °F	0.1 °C (-40 °C ... +140 °C) 0.1 °F (-40 ... +284 °F) 0.2 °C (-50 °C ... -40 °C) 0.4 °F (-58 ... -40 °F)	
 testo 190-T2, testo 191-T2	48 g						
 testo 190-T3, testo 191-T3	61 g						
 testo 190-T4, testo 191-T4	92 g			1 mbar	1 mbar ... 4 bar		
 testo 190-P1, testo 191-P1	91 g						

 testo 190-T1, testo 191-T1	20 x 59 mm	3 x 25 mm	—
 testo 190-T2, testo 191-T2		3 x 115 mm	
 testo 190-T3, testo 191-T3	20 x 63 mm	1,5 x 775 mm	3 x 25 mm
 testo 190-T4, testo 191-T4	20 x 72 mm		
 testo 190-P1, testo 191-P1	22 x 83 mm	—	—

 0515 1901	-50 ... +140 °C -58 ... +284 °F 	750 h



Guideline	2014/30/EU (EMC); 2011/65/EU (RoHS)
EU declaration of conformity	You can find the EU declaration of conformity on the Testo website www.testo.com under the product-specific downloads.

Manufacturer/ importer

Testo SE & Co. KG aA
Celsiusstr. 2, 79822 Titisee-Neustadt, Germany
+49 7653 681-0
www.testo.com

Warning: Please follow the instructions when using the product.